

AccuSpray™ VSS-2000/VSS-3000

DIMENSION

| SPECIFICATION              | VSS-2000                            | VSS-3000                            |
|----------------------------|-------------------------------------|-------------------------------------|
| CAPACITY                   | 200 gal                             | 300 gal                             |
| APPROX. WEIGHT (EMPTY)     | 450 lb                              | 520 lb                              |
| OVERALL DIMENSIONS (LXWXH) | 88" x 82" boom x 64"                | 94" x 82" boom x 68"                |
| FLOOR LENGTH               | 74"                                 | 80"                                 |
| FLOOR WIDTH                | 36"                                 | 39"                                 |
| TANK DIMENSIONS (LXW)      | 47" x 37"                           | 60" x 42"                           |
| SPRAYING WIDTH             | Up to 25'                           | Up to 25'                           |
| SPRAYING VOLUME            | 20 gal per lane mile/acre at 10 mph | 20 gal per lane mile/acre at 10 mph |

CONSTRUCTION

| SPECIFICATION                                           | VSS-2000                            | VSS-3000                            |
|---------------------------------------------------------|-------------------------------------|-------------------------------------|
| VEHICLE COMPATIBILITY<br>Vehicle mounts sold separately | 3/4- or 1-Ton Pickup Truck          | 3/4- or 1-Ton Pickup Truck          |
| WIRING HARNESS                                          | Completely loomed with molded plugs | Completely loomed with molded plugs |
| MOTORS                                                  | 12V direct-drive pumps              | 12V direct-drive pumps              |
| MOUNTING                                                | Straps included                     | Straps included                     |