



DIMENSION

SPECIFICATION	77775	77770	77785	77780
BLADE WIDTH	8'6"	8'6"	9'6"	9'6"
APPROX. WEIGHT Does not include vehicle mount (28 lb - 145 lb weight range). Please refer to the Power Match program for specific vehicle applications.	950 lbs	950 lbs	1,020 lbs	1,020 lbs
PLOWING WIDTH (STRAIGHT)	Straight: 8'6" (9'5" w/ Wings) V: 7'8" (9'7" w/ Wings) Scoop: 7'2" (8'2" w/ Wings)	Straight: 8'6" (9'5" w/ Wings) V: 7'8" (9'7" w/ Wings) Scoop: 7'2" (8'2" w/ Wings)	Straight: 9'6" (10'5" w/ Wings) V: 8'7" (10'6" w/ Wings) Scoop: 8'2" (9'2" w/ Wings)	Straight: 9'6" (10'5" w/ Wings) V: 8'7" (10'6" w/ Wings) Scoop: 8'2" (9'2" w/ Wings)
PLOWING WIDTH (FULL ANGLE)	7'6" (9'7" w/ Wings)	7'6" (9'7" w/ Wings)	8'7" (9'10" w/ Wings)	8'7" (9'10" w/ Wings)
BLADE HEIGHT	At Hinge: 2'7" At End: 3'2"	At Hinge: 2'7" At End: 3'2"	At Hinge: 2'7" At End: 3'3"	At Hinge: 2'7" At End: 3'3"
ANGLE CYLINDERS	1.75" x 11"	1.75" x 11"	1.75" x 11"	1.75" x 11"
CUTTING EDGE	3/8" (Standard)	3/8" (Standard)	1/2" (Standard)	1/2" (Standard)
BLADE THICKNESS	16 ga	16 ga	16 ga	16 ga

CONSTRUCTION

SPECIFICATION	77775	77770	77785	77780
MOLDBOARD OPTIONS	Stainless Steel	Powder-Coated Steel	Stainless Steel	Powder-Coated Steel
BLADE TYPE	V-Plow	V-Plow	V-Plow	V-Plow
VEHICLE COMPATIBILITY Vehicle mounts sold separately	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors	Truck Class 2 - 6 (under 26,000 lb GVWR) & Tractors
REINFORCEMENT RIBS	6 vertical/1 angle	6 vertical/1 angle	8 vertical/1 angle	8 vertical/1 angle
TRIP SPRINGS	4 steel	4 steel	6 steel	6 steel