

Heavy-Duty

DIMENSION

SPECIFICATION	77720-1	77725-1	77730-1	77735-1
BLADE WIDTH	7'6"	8'0"	8'6"	9'0"
APPROX. WEIGHT Does not include vehicle mount (28 lb - 145 lb weight range). Please refer to the Power Match program for specific vehicle applications.	730 lbs	746.5 lbs	763.5 lbs	781.5 lbs
PLOWING WIDTH (STRAIGHT)	7'6" 9'3" (W/ Wings)	8'0" 9'9" (W/ Wings)	8'6" 10'3" (W/ Wings)	9'0" 10'9" (W/ Wings)
PLOWING WIDTH (FULL ANGLE)	6'6" 7'11" (W/ Wings)	6'11" 8'5" (W/ Wings)	7'5" 8'10" (W/ Wings)	7'9" 9'4" (W/ Wings)
BLADE HEIGHT	2'7"	2'7"	2'7"	2'7"
ANGLE CYLINDERS	1-1/2"	1-1/2"	1-1/2"	1-1/2"
CUTTING EDGE	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)	1/2" x 6" (Standard)
BLADE THICKNESS	12 ga	12 ga	12 ga	12 ga

CONSTRUCTION

SPECIFICATION	77720-1	77725-1	77730-1	77735-1
SMART MODEL NUMBERS	7600HD	8000HD	8600HD	9000HD
MOLDBOARD OPTIONS	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel	Powder-Coated Steel
BLADE TYPE	Straight Blade	Straight Blade	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY Vehicle mounts sold separately	Class 2-5 Trucks & 3-4 Series Tractors Class 2-5 Trucks & 3-4 Series Tractors	Class 2-5 Trucks & 3-4 Series Tractors Class 2-5 Trucks & 3-4 Series Tractors	Class 2-5 Trucks & 3-4 Series Tractors Class 2-5 Trucks & 3-4 Series Tractors	Class 2-5 Trucks & 3-4 Series Tractors Class 2-5 Trucks & 3-4 Series Tractors
REINFORCEMENT RIBS	6 vertical/2 angle	6 vertical/2 angle	6 vertical/2 angle	6 vertical/2 angle
TRIP SPRINGS	4 steel	4 steel	4 steel	4 steel