

Utility

DIMENSION

SPECIFICATION	SP-100-1	SP-125-1	SP-225-1	SP-325
CAPACITY (VOLUME)	3.0 cu ft (Electric)	3.0 cu ft (Manual)	3.0 cu ft (Auger)	3.25 cu ft (Auger)
SPREADING WIDTH	Up to 20'	Up to 20'	Up to 25'	Up to 25'
APPROX. WEIGHT (EMPTY)	75 lb	65 lb	68 lb	79 lb
OVERALL DIMENSIONS (LXWXH)	22" x 30" x 30"	22" x 30" x 30"	22" x 30" x 32"	18" x 33" x 33"
HOPPER DIMENSIONS (LXW)	22" x 30"	22" x 30"	22" x 30"	16.5" x 33"
CAPACITY (WEIGHT) Material weight equates to approximately 2,160 lb/cu yd or 80 lb/cu ft (1 bag of rock salt).	240 lb	240 lb	240 lb	260 lb

CONSTRUCTION

SPECIFICATION	SP-100-1	SP-125-1	SP-225-1	SP-325
VEHICLE COMPATIBILITY Vehicle mounts sold separately	1/2, 3/4, or 1-Ton Pickup Trucks, UTVs & Tractors	1/2, 3/4, or 1-Ton Pickup Trucks, UTVs & Tractors	1/2, 3/4, or 1-Ton Pickup Trucks, UTVs & Tractors	1/2, 3/4, or 1-Ton Pickup Trucks, UTVs & Tractors
MATERIAL COMPATIBILITY	Fine Materials	Fine Materials	Bagged Salt	Bagged Salt
MOTORS	Dual Electric, 12V, Sealed	Dual Electric, 12V, Sealed	Dual Electric, 12V, Sealed	Dual Electric, 12V, Sealed
SPINNER	10"	10"	10"	10"
AUGER	N/A	N/A	3" vertical high-flow auger	3" vertical high-flow auger
FEEDGATE	Electronically Controlled	Manual	N/A	N/A
WIRING HARNESS	12-gauge with molded plugs and connectors	Multiple gauge harness with plug-ends and finished connectors	Automotive style with plug-ends and finished connectors	Completely loomed with molded plugs