

Mid-Duty UTV Straight Blade

DIMENSION

SPECIFICATION	87520 - Hydraulic	87520 - Winch	87521 - Hydraulic	87521 - Winch
BLADE WIDTH	5'6"- Hydraulic	5'6" - Winch	6'0" - Hydraulic	6'0" - Winch
APPROX. WEIGHT Does not include vehicle mount (28 lb - 145 lb weight range). Please refer to the Power Match program for specific vehicle applications.	195 lbs	170 lbs	195 lbs	175 lbs
PLOWING WIDTH (STRAIGHT)	4'11"	4'11"	5'4"	5'4"
BLADE HEIGHT	1'8"	1'8"	1'8"	1'8"
LIFT CYLINDER (SINGLE ACTING) Lift Cylinder only available for hydraulic models.	1.5" x 3" (one)	N/A	1.5" x 3" (one)	N/A
BLADE THICKNESS	16 ga	16 ga	16 ga	16 ga

CONSTRUCTION

SPECIFICATION	87520 - Hydraulic	87520 - Winch	87521 - Hydraulic	87521 - Winch
SMART MODEL NUMBERS	6000MD	6000MD	7200MD	7200MD
MOLDBOARD OPTIONS	High-Strength Steel	High-Strength Steel	High-Strength Steel	High-Strength Steel
BLADE TYPE	Straight Blade	Straight Blade	Straight Blade	Straight Blade
VEHICLE COMPATIBILITY Vehicle mounts sold separately	Mid Sized, Crossover & Sport UTVs	Mid Sized, Crossover & Sport UTVs	Mid Sized, Crossover & Sport UTVs	Mid Sized, Crossover & Sport UTVs
ANGLING RAMS (DOUBLE ACTING) Angling Ram only available for hydraulic models.	1.5" x 4"	N/A	1.5" x 4"	N/A
CUTTING EDGE	1/4" x 4" (Standard)	1/4" x 4" (Standard)	1/4" x 4" (Standard)	1/4" x 4" (Standard)
VERTICAL RIBS	4	4	4	4
TRIP SPRINGS	2	2	2	2
MOUNT TYPE	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System	Mid-Duty UTV Mounting System