Utility Specifications

Imperial	SP-100-1	SP-125-1	SP-225-1	SP-325
Vehicle Compatibility	½, ¾, or 1-Ton Pickup	½, ¾, or 1-Ton Pickup	1/2, 3/4, or 1-Ton Pickup	½, ¾, or 1-Ton Pickup
	Trucks, UTVs & Tractors	Trucks, UTVs & Tractors	Trucks, UTVs & Tractors	Trucks, UTVs & Tractors
Material Compatibility	Bagged Ice Melters,	Bagged Ice Melters,	Bagged Salt	Bagged Salt
	Calcium Chloride Pellets,	Calcium Chloride Pellets,		
	Calcium Flakes	Calcium Flakes		
Capacity (Volume)	3.0 cu ft	3.0 cu ft	3.0 cu ft	3.25 cu ft
Spreading Width	Up to 20'	Up to 20'	Up to 25'	Up to 25'
Approx. Weight (Empty)	75 lb	65 lb	68 lb	79 lb
Overall Dimensions	22" x 30" x 30"	22" x 30" x 30"	22" x 30" x 32"	18" x 33" x 33"
(LxWxH)				
Hopper Dimensions	22" x 30"	22" x 30"	22" x 30"	16.5" x 33"
(LxW)				
Capacity (Weight)*	240 lb	240 lb	240 lb	260 lb
Motors	Dual Electric, 12V,	Dual Electric, 12V,	Dual Electric, 12V,	Dual Electric, 12V,
	Sealed	Sealed	Sealed	Sealed
Spinner	10"	10"	10"	10"
Auger	N/A	N/A	3" vertical high-flow	3" vertical high-flow
			auger	auger
Feedgate	Electronically Controlled	Manual	N/A	N/A
Wiring Harness	12-gauge with molded	Multiple gauge harness	Automotive style with	Completely loomed with
	plugs and connectors	with plug-ends and	plug-ends and finished	molded plugs
		finished connectors	connectors	

Metric	SP-100-1	SP-125-1	SP-225-1	SP-325
Models	SP-100-1	SP-125-1	SP-225-1	SP-325
Vehicle Compatibility	½, ¾, or 1-Ton Pickup	½, ¾, or 1-Ton Pickup	1/2, 3/4, or 1-Ton Pickup	½, ¾, or 1-Ton Pickup
	Trucks, UTVs & Tractors			
Material Compatibility	Bagged Ice Melters,	Bagged Ice Melters,	Bagged Salt	Bagged Salt
	Calcium Chloride Pellets,	Calcium Chloride Pellets,		
	Calcium Flakes	Calcium Flakes		
Capacity (Volume)	0.085 cu m	0.085 cu m	0.085 cu m	0.092 cu m
Spreading Width	Up to 6.1 m	Up to 6.1 m	Up to 7.6 m	Up to 7.6 m
Approx. Weight (Empty)	34.0 kg	29.5 kg	30.8 kg	35.8 kg
Overall Dimensions	55.9 cm x 76.2 cm x 76.2	55.9 cm x 76.2 cm x 76.2	55.9 cm x 76.2 cm x 81.3	45.7 cm x 83.8 cm x 83.8
(LxWxH)	cm	cm	cm	cm
Hopper Dimensions	55.9 cm x 76.2 cm	55.9 cm x 76.2 cm	55.9 cm x 76.2 cm	41.9 cm x 83.8 cm
(LxW)				
Capacity (Weight)*	108.9 kg	108.9 kg	108.9 kg	117.9 kg
Motors	Dual Electric, 12V,	Dual Electric, 12V,	Dual Electric, 12V,	Dual Electric, 12V,
	Sealed	Sealed	Sealed	Sealed
Spinner	25.4 cm	25.4 cm	25.4 cm	25.4 cm
Auger	N/A	N/A	7.6 cm vertical high-flow	7.6 cm vertical high-flow
			auger	auger
Feedgate	Electronically Controlled	Manual	N/A	N/A

Utility Specifications

Wiring Harness	12-gauge with molded	Multiple gauge harness	Automotive style with	Completely loomed with
	plugs and connectors	with plug-ends and	plug-ends and finished	molded plugs
		finished connectors	connectors	

^{*}Material weight equates to approximately 2,160 lb/cu yd or 80 lb/cu ft (1 bag of rock salt).