

## Construction

<b>Imperial</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	Dual 12-volt DC direct-drive motors mounted in weather resistant enclosure	Dual 12-volt DC direct-drive motors mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	10" nylon/glass reinforced resin	12" powder coated steel
Auger Drive Assembly	Heavy-duty solid steel construction with maximum torque motor transmission drive	Heavy-duty solid steel construction with maximum torque motor transmission drive
Auger	Horizontal high-flow auger	Horizontal high-flow auger
Mounting	Receiver mount and 3-Point mount combination standard	Mount not included. (Receiver, 3-point or pivot mount optional)

<b>Metric</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Frame	Powder coated steel	Powder coated steel
Hopper	One-piece LLDPE safety yellow poly	One-piece LLDPE safety yellow poly
Motors	Dual 12-volt DC direct-drive motors mounted in weather resistant enclosure	Dual 12-volt DC direct-drive motors mounted in weather resistant enclosure
Spinner Drive Assembly	Maximum torque transmission with hardened-steel worm and bronze gear	Maximum torque transmission with hardened-steel worm and bronze gear
Spinner	25.4 cm nylon/glass reinforced resin	30.5 cm powder coated steel
Auger Drive Assembly	Heavy-duty solid steel construction with maximum torque motor transmission drive	Heavy-duty solid steel construction with maximum torque motor transmission drive
Auger	Horizontal high-flow auger	Horizontal high-flow auger
Mounting	Receiver mount and 3-Point mount combination standard	Mount not included. (Receiver, 3-point or pivot mount optional)

## Dimensions

<b>Imperial</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Approx. Weight (Empty)	160 lb	180 lb
Overall Length	20.5"	24"
Overall Height	34"	36"
Overall Width	38"	52"
Hopper Length	20.5"	21"
Hopper Width	38"	47"

<b>Metric</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Approx. Weight (Empty)	72.6 kg	81.7 kg
Overall Length	52.1 cm	60.9 cm
Overall Height	86.4 cm	91.4 cm
Overall Width	96.5 cm	132.1 cm
Hopper Length	52.1 cm	53.3 cm
Hopper Width	96.5 cm	119.4 cm

### Electrical

<b>Imperial</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Speed Control	Digital, self-diagnosing variable speed control	Digital, self-diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

<b>Metric</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Speed Control	Digital, self-diagnosing variable speed control	Digital, self-diagnosing variable speed control
Wiring Harness	Completely loomed with molded plugs	Completely loomed with molded plugs

### Operational

<b>Imperial</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Capacity (Volume)	5.25 cu ft	9.0 cu ft
Capacity (Weight)*	420 lb	720 lb
Spreading Width	Up to 30'	Up to 40'

<b>Metric</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Capacity (Volume)	0.149 cu m	0.254 cu m
Capacity (Weight)*	190.5 kg	326.6 kg
Spreading Width	Up to 9.2 m	Up to 12.2 m

### Standard Equipment

<b>Imperial</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Top Screen	1/4" steel rod construction with grid pattern	1/4" steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Standard	Standard
Inverted	Patented vibrating inverted "V" to maximize material flow	Patented vibrating inverted "V" to maximize material flow

<b>Metric</b>	<b>SP-1575-1</b>	<b>SP-1875-1</b>
Top Screen	0.6 cm steel rod construction with grid pattern	0.6 cm steel rod construction with grid pattern
Cover	Fitted lid	Fitted lid
Vibrator	Standard	Standard
Inverted	Patented vibrating inverted "V" to maximize material flow	Patented vibrating inverted "V" to maximize material flow